

BASKET S3

KU037N

CE UNI EN ISO 20345:2012 S3 SRC ESD

ANKLE SAFETY SHOE

36-47

KUBE Supergrip

High safety shoe, Nubuck IDROTECH® WRU grain leather thickness 1,8-2,0 mm. Perspiring and resistant to abrasion fabric lining.

Shoe with refracting fabric insert.

Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015**

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial







The shoe satisfies the requirement according to the norm IEC 61340-4-3:2001 for the electrical resistance

ESD







Size 36-47 Shoe weight Sz 42 gr. 570* *The calculated weight excludes laces and insoles.*



→ **AREAS OF APPLICATION**

-  Sloped Roofs
-  Construction and Building Sites
-  Logistics and Light Industry
-  Automotive Components
-  Metal and Wood Carpentry
-  ESD Area

→ **CERTIFICATIONS APPLIED**

-  Antistatic Footwear
-  Slip Resistant Sole
-  Heel Energy Absorption
-  Hydrocarbon Resistance
-  Water-Repellent Upper
-  DGVU 112-191

→ **TECHNOLOGIES AND MATERIALS**

-  No metal
-  ESD - Electrostatic Discharge
-  Metal-Free
-  High Visibility
-  Highly Breathable and Water-Repellent Leather
-  Mondo Point 11
-  Extreme Lightness
-  Slip Resistance on Inclined Roofs

→ **ANTI-SLIP RESULTS**

*after simulation of walking by slight abrasion

Ceramic tile floor with NaLS	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31 ≥ 0.56	≥ 0.36 ≥ 0.45		≥ 0.19 ≥ 0.35	≥ 0.22 ≥ 0.35
SRA Ceramic + Nails	Flat	Heel	SRB Steel + Glycerol	Flat	Heel
	≥ 0.32 ≥ 0.39	≥ 0.28 ≥ 0.37		≥ 0.18 ≥ 0.30	≥ 0.13 ≥ 0.20

↳ PLUS



Highly Breathable and Water-Repellent Leather

Idrotech® leather undergoes a special treatment that combines waterproof and breathability, ensuring comfort in all seasons and protection from external elements. This technology allows work shoes to keep feet dry without sacrificing internal ventilation, making them ideal for outdoor environments and variable conditions.

↳ SOLE

KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slipperiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

