

# SOFTBALL S3L FO SR

KU037T

CE EN ISO 20345:2022 S3L FO SR ESD

**ANKLE SAFETY SHOE**

**39-47**

**KUBE** Supergrip

High safety shoe, suede back WPA leather thickness 1,8-2,0 mm.  
Highly perspiring and abrasion resistant fabric lining.  
Shoe with refracting fabric insert.  
Soft, lined and padded tongue.

**COMPLETELY METAL FREE SHOE**

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015** (test report. 4312114 E)

**TOECAP 200J** polymeric composite non-thermic according to EN 22568

**PL MIDSOLE** flexible antiperforation composite fabric according to EN 22568

**SOLE KUBE** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping

**INSOLE 5000** three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

**FO** sole resistance to hydrocarbons

**SR** slip resistance

**Size 39-47 Shoe weight Sz 42 gr. 600**

*\* The calculated weight excludes laces and insoles.*



## AREAS OF APPLICATION

- Sloped Roofs
- Logistics and Light Industry
- Automotive Components
- Metal and Wood Carpentry
- ESD Area

## CERTIFICATIONS APPLIED

- Water Penetration and Absorption (WPA)
- PL Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)
- Slip Resistance (mandatory ceramic-Nails test)
- Antistatic Footwear
- Heel Energy Absorption
- Hydrocarbon Resistance

## TECHNOLOGIES AND MATERIALS

- No metal
- ESD - Electrostatic Discharge
- Metal-Free
- High Visibility
- Mondo Point 11
- Extreme Lightness
- Slip Resistance (optional glycerin test)
- Slip Resistance on Inclined Roofs

## ANTI-SLIP RESULTS

*\*after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	<b>Forward heel</b> (heel slip 7°)	<b>Backward heel</b> (heel slip 7°)	Ceramic tile floor with glycerin	<b>Forward heel</b> (heel slip 7°)	<b>Backward heel</b> (heel slip 7°)
	≥ 0.31    ≥ 0.56	≥ 0.36    ≥ 0.45		≥ 0.19    ≥ 0.35	≥ 0.22    ≥ 0.35
SRA Ceramic + Nails	<b>Flat</b>	<b>Heel</b>	SRB Steel + Glicerol	<b>Flat</b>	<b>Heel</b>
	≥ 0.32    ≥ 0.39	≥ 0.28    ≥ 0.37		≥ 0.18    ≥ 0.30	≥ 0.13    ≥ 0.20

↳ SOLE

## KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slipperiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

