



GYM EVO S3L FO SR

3M037NG

CE EN ISO 20345:2022 S3L FO SR ESD

ANKLE SAFETY SHOE

36-47

3MOVE Ergonomic

High safety shoe, MICRO-tech technical fabric thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.
COMPLETELY METAL FREE SHOE
TOECAP 200J polymeric composite **non-thermic** according to EN 22568
PL MIDSOLE flexible antiperforation composite fabric according to EN 22568
SOLE 3MOVE three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping
ANTITORSION insert in the sole to assure stability on uneven ground
INSOLE MEMORY, extra comfort trimaterial insole with soft PU Memory foam cushion that relieves fatigue in the heel and resists body pressure. Breathable, removable, anatomical, absorbent, antibacterial, and ESD.
The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance ESD
FO sole resistance to hydrocarbons
SR sole resistance against slipping
Size 36-47 **Shoe weight** Sz 42 **gr. 560**



AREAS OF APPLICATION

-  Sloped Roofs
-  Construction and Building Sites
-  Logistics and Light Industry
-  Automotive Components
-  Metal and Wood Carpentry
-  ESD Area

CERTIFICATIONS APPLIED

-  Water Penetration and Absorption (WPA)
-  PL Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)
-  Slip Resistance (mandatory ceramic-Nals test)
-  Antistatic Footwear
-  Heel Energy Absorption
-  Hydrocarbon Resistance
-  DGUV 112-191

TECHNOLOGIES AND MATERIALS

-  No metal
-  Patented Outsole Design
-  ESD - Electrostatic Discharge
-  High Visibility
-  Mondo Point 11
-  Extreme Lightness
-  Slip Resistance (optional glycerin test)
-  Slip Resistance on Inclined Roofs
-  Microtech
-  Three to be™ - Triple Density Injection
-  Memory Foam Insole

ANTI-SLIP RESULTS

*after simulation of walking by slight abrasion

Ceramic tile floor with NaLS	Forward Heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward Heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31 ≥ 0.37	≥ 0.36 ≥ 0.45		≥ 0.19 ≥ 0.34	≥ 0.22 ≥ 0.29



Three to be™ - Triple Density Injection

Three to Be® - Tripla Densità Iniettata technology represents one of the most advanced results of our R&D efforts. Patented by Giasco, it integrates three entirely polyurethane-injected sole layers to optimize safety shoe performance in terms of comfort, stability, and slip resistance.



Memory Foam Insole

The MEMORY FOAM insole offers superb comfort thanks to its innovative material, which adapts to foot shape. It enhances walking comfort, supports posture, improves fit, and distributes body weight. Additionally, it stabilizes the foot and absorbs ground impact, serving as an excellent shock absorber.

3MOVE Ergonomic

3Move is a revolutionary line that, thanks to the rounded design of the sole, ensures correct body posture while walking. This curvature allows for even weight distribution across the entire foot, providing relief to the back, knees, and heels. This line is the ideal work shoe for relieving workers who suffer from such discomfort. 3Move is therefore the only ergonomic shoe in the industry designed to meet these needs while also ensuring complete protection. Another feature of this line is the heel relief area, which, thanks to its cavity, offers perfect weight cushioning. Ultimately, all these aspects contribute to significant energy and effort savings for the worker at the end of the day. The tread, on the other hand, is designed for indoor environments. This is made possible by a dense pattern of lugs that together ensure high anti-slip performance for this safety footwear.

