

HAMBURG S7L FO CI SR

AC058L

CE EN ISO 20345:2022 S7L FO CI SR

ANKLE SAFETY SHOE

36-49

ACTION Essential

High safety shoe, full-grain IDROTECH® WPA leather, thickness 1.8-2.0 mm, with refracting insert.

Heel are with WPA anti-scratch back leather thickness 1,8-2,0 mm.

Soft Windtex® water resistant membrane lining, with very good perspiration and abrasion resistance.

Soft, lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 22568

MIDSOLE PL flexible antiperforation composite fabric according to EN 22568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping

INSOLE EASY 4001, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: the values found prove that this insole is ESD

CI cold insulation of sole complex -17°C

WR water resistant shoe

SR sole resistance against slipping



Size 36-49 Shoe weight Sz 42 gr. 625

** The calculated weight excludes laces and insoles.*

→ **AREAS OF APPLICATION**

- Farming and Agriculture
- Cold Environments
- Construction and Building Sites
- Logistics and Light Industry
- Automotive Components

→ **CERTIFICATIONS APPLIED**

- Water Penetration and Absorption (WPA)
- PL Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)
- Slip Resistance (mandatory ceramic-Nails test)
- Antistatic Footwear
- Heel Energy Absorption
- Hydrocarbon Resistance
- Water-Repellent Footwear
- DGVU 112-191

→ **TECHNOLOGIES AND MATERIALS**

- No metal
- WindTex® Membrane
- High Visibility
- Highly Breathable and Water-Repellent Leather
- Mondo Point 11
- Extreme Lightness
- Cold Insulating Outsole
- Slip Resistance (optional glycerin test)

→ **ANTI-SLIP RESULTS**

**after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31 0.43	≥ 0.36 0.48		≥ 0.19 0.31	≥ 0.22 0.26
SRA Ceramic + Nails	Flat	Heel	SRB Steel + Glicerol	Flat	Heel
	≥ 0.32 0.37	≥ 0.28 0.33		≥ 0.18 0.22	≥ 0.13 0.24

↳ PLUS



WindTex® Membrane

The Windtex® membrane is a technology designed to block water and wind. Lightweight and elastic, it provides comfort and protection throughout the workday while maintaining a stable microclimate between the skin and fabric. Thanks to its high breathability, it is ideal for breathable safety shoes that need to prevent overheating and excessive sweating even in winter or during long shifts.



Highly Breathable and Water-Repellent Leather

Idrotech® leather undergoes a special treatment that combines waterproof and breathability, ensuring comfort in all seasons and protection from external elements. This technology allows work shoes to keep feet dry without sacrificing internal ventilation, making them ideal for outdoor environments and variable conditions.

↳ SOLE

ACTION Essential

The Action line is designed for those who work outdoors every day and need a shoe that is simple yet effective. With soft lines and a lightweight structure, it offers a minimal design that prioritizes comfort and practicality without compromising on safety. Perfect for daily tasks and light maintenance, these shoes support every step without weighing you down.

