

CAMBRIDGE S3

AC068D

CE UNI EN ISO 20345:2012 S3 SRC

ANKLE SAFETY SHOE

36-51

ACTION Essential

High safety shoe, WRU back leather thickness 1,8-2,0 mm.
 Perspiring and abrasion resistant fabric lining.
 Shoe with refracting fabric insert.
 Soft, lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE EASY 4001, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

Size 36-51 Shoe weight Tg 42 gr. 615

** The calculated weight excludes laces and insoles.*



→ **AREAS OF APPLICATION**

- Farming and Agriculture
- Construction and Building Sites
- Logistics and Light Industry
- Automotive Components
- Metal and Wood Carpentry

→ **CERTIFICATIONS APPLIED**

- Antistatic Footwear
- Slip Resistant Sole
- Heel Energy Absorption
- Hydrocarbon Resistance
- Water-Repellent Upper

→ **TECHNOLOGIES AND MATERIALS**

- No metal
- High Visibility
- Mondo Point 11
- Extreme Lightness

→ **ANTI-SLIP RESULTS**

**after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31 0.43	≥ 0.36 0.48		≥ 0.19 0.31	≥ 0.22 0.26
SRA Ceramic + Nails	Flat	Heel	SRB Steel + Glicerol	Flat	Heel
	≥ 0.32 0.37	≥ 0.28 0.33		≥ 0.18 0.22	≥ 0.13 0.24

↳ SOLE

ACTION Essential

The Action line is designed for those who work outdoors every day and need a shoe that is simple yet effective. With soft lines and a lightweight structure, it offers a minimal design that prioritizes comfort and practicality without compromising on safety. Perfect for daily tasks and light maintenance, these shoes support every step without weighing you down.

